

CASH VALVE™ A SERIES PRESSURE REGULATORS

A360, A361, A365 SELECTION GUIDE

Example:	A360	A	W	S	Z	S	B	B	S	01	-	D	1
Model	A360	A360											
A361	A361												
A365	A365												
Size													
A	1/4"												
B	3/8"												
C	1/2" (A360, A361)												
Service													
W	Water/air												
Body/connection style													
S	Side inlet / side outlet - straight thru (A360, A365)												
X	Side inlet / side outlet - straight thru w/ two 1/4" gauge ports (A361)												
Spring chamber material													
Z	Bronze spring chamber												
Spring chamber style													
S	Standard												
P	Panel mount (A360, A361)												
D	Differential connection and adjusting screw cap (A365)												
C	Adjusting screw cap (A365)												
Diaphragm material													
B	Buna-N (A360, A365)				Z	Bronze							
L	Buna-N w/ Teflon liner (A360 and A365)				V	Viton							
N	Neoprene				E	EPDM (A365)							
T	Neoprene w/ Teflon liner (A360)												
Seat material													
B	Buna-N				N	Neoprene (A365)							
T	Teflon (A360, A361)				E	EPDM (A365)							
V	Viton												
Pressure screw style													
S	Standard												
T	T-handle												
H	Hex												
Variation													
01	Standard												
Design revision													
(-)	Original design												
Spring material													
E	Stainless steel												
Spring range													
	Refer to table below												

NOTE

NPTF, also referred to as 'Dryseal' thread, is designed to provide a more leak-free seal without the use of PTFE tape or other sealant compound. NPTF threads are interchangeable with NPT threads and are standard on all Cash Valve products.

STANDARD SPRING RANGES (psig)

Spring Material	Type	Size	0	1	2	3	4	5	6	7
SST	A360	1/4", 3/8"	No spring	0 - 5	2 - 35	20 - 70	60 - 125	75 - 200	100 - 250	----
	A361	1/4", 3/8"	----	0 - 5	2 - 35	20 - 70	60 - 125	75 - 200	100 - 250	200 - 400
	A360, A361	1/2"	No spring*	0 - 5	2 - 25	20 - 60	40 - 80	75 - 125	100 - 250	----
	A365	All sizes	----	0 - 40	40 - 80	25 - 150	100 - 200	200 - 250	200 - 400	----

* Only available for A360